

PW 504409 T

Order No : 4901884

<b>Component type</b>	Inspection Protection window
<b>Material</b>	Polycarbonate
<b>Gasket material</b>	Polyurethane
<b>Country of origin</b>	Finland



### Temperatures °C

Temperature °C : -40 ... +80

### Ratings :

Degree of protection	IP66 - EN 60529
Impact resistance	IK09 - EN 62262
Electrical insulation	Total insulated
Halogen free	Yes ( DIN / VDE 0472,Part 815 )
UV resistance	UL 746°
Flammability Rating	UL 94 V0
Glow Wire Test	IEC 60695 : 960°
UL Type	4, 4X, 12 and 13

### Dimensional Drawings

Width ( mm )	503
Height ( mm )	451
Depth ( mm )	88

### Downlight

Dimensional drawing - pdf	<a href="https://www.fibox.com/hubfs/assets/4901844_FIBOX_PW_504409_T%20DIM.pdf">https://www.fibox.com/hubfs/assets/4901844_FIBOX_PW_504409_T%20DIM.pdf</a>
Dimensional drawing - dwg	<a href="https://www.fibox.com/hubfs/assets/4901844_FIBOX_PW_504409_T%20DIM.dwg">https://www.fibox.com/hubfs/assets/4901844_FIBOX_PW_504409_T%20DIM.dwg</a>
Dimensional drawing - step	<a href="https://www.fibox.com/hubfs/assets/4901844_FIBOX_PW_504409_T.step">https://www.fibox.com/hubfs/assets/4901844_FIBOX_PW_504409_T.step</a>